

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 September 2005 (15.09.2005)

PCT

(10) International Publication Number
WO 2005/085729 A2

(51) International Patent Classification⁷: **F26B 3/28**

(74) Agent: **VAN STEENLANDT, Wim**; Bekaertstraat 2,
B-8550 ZWEVEGEM (BE).

(21) International Application Number:
PCT/EP2005/050731

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.

(22) International Filing Date: 21 February 2005 (21.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0402139 2 March 2004 (02.03.2004) FR

(71) Applicants (for all designated States except US): **NV
Bekaert SA** [BE/BE]; Bekaertstraat 2, B-8550 ZW-
EVEGEM (BE). **Bekaert Combustion Technology NV**
[BE/BE]; Bekaertstraat 2, B-8550 ZWEVEGEM (BE).


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **LENOIR, Patrick**
[FR/FR]; 37, rue Cendrillon, F-59650 VILLENEUVE
D'ASCQ (FR).

[Continued on next page]

(54) Title: **DRIER INSTALLATION FOR DRYING WEB**



(57) Abstract: A drier installation (1) for drying web (2), more particularly paper, which installation is provided for drying a maximum web width, the installation (1) comprises gas-heated radiant elements (3) for radiating the web, arranged according to at least one row (4) stretching out in the transversal (5) direction over the substantially entire maximum web width. The installation (1) comprises at least a transversal convective system (7, 36) equipped with suction and blowing devices (8) for sucking at least part of the combustion products produced by the radiant elements (3) by means of a suction duct (13) and for blowing this part of the combustion products towards the web (2) by means of a blowing duct (14). Both suction (13) and blowing (14) ducts stretch out in the transversal (5) direction of the web (2). The convective system (7, 36) comprising at least a mixing device (12, 22, 28, 37, 46) is installed opposite of the passing web (2) in relation to corresponding suction (13) and blowing (14) ducts and arranged so as to suck and/or blow the combustion products. The

drier installation as subject of the present invention is characterized in that the vector average of the projections (V1, V2, V3, V5, V6, V7, V8) in a plane (P1) perpendicular to the web (2) and stretching out in the transversal (5) direction of the web (2), has component (V4) parallel to the web (2) that is smaller than the maximum web width of the web (2), the vectors representing the respective trajectories of the different jets of sucked and/or blown combustion products.



Published:

— *without international search report and to be republished
upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.